

Number of Components:	<u>Two</u>	<u>Frozen Syringe</u>	Minimum Bond Line Cure Schedule*:	
Mix Ratio By Weight:	10:1		150°C	1 Minute
Specific Gravity:		1.18	120°C	5 Minutes
Part A	1.20		100°C	10 Minutes
Part B	1.02		80°C	30 Minutes
Pot Life:	≤ 3 Hours	2 Hours		
Shelf Life:	One year at 23°C	Six months at -40°C		

Note: Container(s) should be kept closed when not in use. *Please see Applications Note available on our website.

-TOTAL MASS SHOULD NOT EXCEED 25 GRAMS -

-- IF PART A CRYSTALLIZES IN STORAGE, PLACE CONTAINER IN A WARM OVEN UNTIL CRYSTALLIZATION DISAPPEARS. ALLOW TO COOL TO ROOM TEMPERATURE BEFORE MIXING WITH THE PART B HARDENER *Please refer to Tech Tip #7 on our website --

Product Description:

EPO-TEK[®] 353ND is a two component, high temperature epoxy designed for semiconductor, hybrid, fiber optic, and medical applications. It is one of the most popular EPO-TEK[®] brand products, and is known throughout the world for its performance and reliability. Also available in a single component frozen syringe.

EPO-TEK[®] 353ND Advantages & Application Notes:

- Reasonable pot-life that allows for low temperature curing to be realized. It has an amber color change upon cure.
- Passes NASA low outgassing standard ASTM E595 with proper cure - <http://outgassing.nasa.gov/>
- Semiconductor suggested applications: wafer-wafer bonding of CSP; fabrication of MEMs devices; flip chip underfill.
- Hybrid suggested applications: providing near hermetic seals and UHV seals in sensor devices, resisting high temperature packaging
 - Down-Hole petrochemical fiber optic sensors, resisting >200°C field conditions
- Fiber optic adhesive designed to meet Telecordia 1221 - suggested applications:
 - Sealing fiber into ferrules, transmitting light in the optical pathway from 800- 1550 nm range
 - Fiber component packaging; adhesive for active alignment of optics, environmental seal of opto-package, V-groove arrays
- Medical suggested applications:
 - Potting fiber optic bundles into ferrules for light guides and endoscopes; capable of resisting several sterilization techniques including ETO, gamma, ION beam, H2O2 plasma, and >200 autoclave steam cycles; excellent adhesion to surfaces including SST, diamond, titanium, brass, ceramics, glass and most plastics.
 - Certified to USP Class VI Biocompatibility Standards for medical implants; adhesive for catheter devices including stents and guide wires
- Electronics Assembly suggested applications:
 - Used as dielectric layer in the fabrication of capacitors; laminating PZT ferroelectrics found in ultrasound or ink-jetting devices
 - Impregnating and insulating copper coil windings in motors and inductor coils. Bonding ferrite cores and magnets.
 - Structural grade epoxy found in hard-disk drive devices; bonding of SST metals, kapton, and magnets

Typical Properties: (To be used as a guide only, not as a specification. Data below is not guaranteed. Different batches, conditions and applications yield differing results; Cure condition: 150°C/1 hour; * denotes test on lot acceptance basis)

Physical Properties:

*Color: Part A: Clear (Gardner <5) Part B: Amber (Gardner <18)

*Consistency: Pourable liquid

*Viscosity (@ 50 RPM/23°C): 3,000 – 5,000 cPs

Thixotropic Index: N/A

*Glass Transition Temp.(Tg): ≥ 90°C (Dynamic Cure
20—200°C /ISO 25 Min; Ramp -10—200°C @ 20°C/Min)

Coefficient of Thermal Expansion (CTE):

Below Tg: 54 x 10⁻⁶ in/in/°C

Above Tg: 206 x 10⁻⁶ in/in/°C

Shore D Hardness: 85

Lap Shear Strength @ 23°C: > 2,000 psi

Die Shear Strength @ 23°C: ≥ 15 Kg / 5,100 psi

Degradation Temp. (TGA): 412°C

Weight Loss:

@ 200°C: 0.22%

@ 250°C: 0.39%

@ 300°C: 0.87%

Operating Temp:

Continuous: - 55°C to 250°C

Intermittent: - 55°C to 350°C

Storage Modulus @ 23°C: 516,912 psi

Ions: Cl⁻ 329 ppm

Na⁺

NH₄⁺ 409 ppm

K⁺ 5 ppm

Particle Size: N/A

Optical Properties @ 23°C:

Refractive Index @ 23°C (uncured): 1.5694 @ 589 nm

Spectral Transmission: > 50% @ 550 nm; > 98% @ 800-1000 nm
> 95% @ 1100 - 1600 nm

Electrical & Thermal Properties:

Thermal Conductivity: N/A

Dielectric Constant @ 23°C (1 KHz): 3.17

Volume Resistivity @ 23°C: ≥ 1.8 x 10¹³ Ohm-cm

Dissipation Factor @ 23°C (1 KHz): 0.005

EPOXY TECHNOLOGY, INC.

14 Fortune Drive, Billerica, MA 01821-3972 Phone: 978.667.3805 Fax: 978.663.9782

www.EPOTEK.com

Epoxy and Adhesives for Demanding Applications™

This information is based on data and tests believed to be accurate. Epoxy Technology, Inc. makes no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with any use of this product.