

NOTES:

- A. 8-32 tapped, threads on both sides. Drill hole through part, and tap through, or tap at least 0.375" usable thread on each side. (x11)
- B. 2-56 clearance through with counterbore to 0.970" deep (leaving 0.030" of material to bottom of part). (x4)
- C. Plunge holes \varnothing 0.250" at these locations first, before cutting out inner cavity. See additional note 3.
- D. Hole \varnothing 0.250", 0.625" deep. Details of bottom not important. (x3)
- E. Hole \varnothing 0.250", 0.809" deep. Details of bottom not important.
- F. Rectangular cavity 0.450" x 0.250" x 0.655" deep (through holes J), corner fillets \varnothing 0.125".
- G. Hole \varnothing 0.177" through part.
- H. 0.450" x 0.250" rectangular slot (with \varnothing 0.250" fillets) through to main cavity (2" deep). In addition, 0.675" x 0.375" rectangular slot (with \varnothing 0.375" fillets) through to prism pocket (0.25" deep).
- I. 8-32 tapped, 0.400" deep. Details of bottom not important.
- J. Rectangular cavity 0.800" x 0.450" x 1.250" deep, corner fillets \varnothing 0.250".
- K. Holes \varnothing 0.063" through to cavity F (1.43" deep). Predrill 1.25" deep so bit won't wander. These holes should be made before cavity J is cut. (x5)
- L. Drill hole \varnothing 0.190", 2.0" deep; details of bottom not important. Then ream \varnothing 0.250", 0.040" deep, flat bottom. External feature is a 0.33" tall, \varnothing 0.372" cylinder which has a channel cut using a 1/32" radius milling cutter. This channel is centered 0.190" from end of feature and has a depth of 0.017".
- M. Drill hole for 8-32 loose (\varnothing 0.185") clearance through to inner cavity. Then counterbore to \varnothing 0.332", 1.610" deep, flat bottom. Then counterbore \varnothing 0.500", 0.425" deep relief with flat bottom, and \varnothing 0.625", 0.375" deep counterbore. Tap hole 3/8-24 so usable threads extend to at least 1" below outermost surface of part. (x2)
- N. 4-40 tapped, at least 0.25" usable thread. Details of bottom not important(x2)
- O. Hole angled 45° with respect to back surface, centered on hole D, and 0.688" below top of piece. All depths measured from top right corner. First drill through to main cavity \varnothing 0.345 \pm 0.001". Then counterbore \varnothing 0.500", 0.696" deep relief with flat bottom and \varnothing 0.625", 0.647" deep counterbore. Tap as in M.
- P. \varnothing 0.070" hole through part. (Cut after arm has been machined to 0.5" thick.) (x8)

UNIBODY LITTROW LASER -- MAIN CAVITY

E. COOK, P. MARTIN, D. STECK


3/24/11

ADDITIONAL NOTES:

1. Material is 6061-T6 aluminum. Starting block is 4.83" x 6" x 1".
2. Standard tolerance is 0.005" unless otherwise noted.


3. Cut holes A and B first. Secure part to supporting base using holes A (to support part) and holes B (to support arm), then cut main cavity through part, plunging first at locations C.
4. Surfaces marked "contact surface" must be made very flat (finishing pass with end mill, as little chatter as possible).
5. See attached drawing for selected details (ramp and arm).

RAMP DETAIL



33.69 degree angle cut made using Ø 0.25" end mill from above. Use many repeated CNC passes to make ramp as smooth as possible.

ARM DETAIL




(Dimensions measured from lower left hand corner of cavity body)

UNIBODY LITTROW LASER -- SELECTED DETAIL

E. COOK, P. MARTIN, D. STECK

2/24/10

TOP VIEW




NOTES:

- A: 8-32 clearance (Ø 0.177") through part with Ø 0.313" counterbore, 0.164" deep from bottom; for mounting lower lid to baseplate.
- B: Ø 0.313" through part (to clear screws which attach the lower lid to the main cavity).
- C: 1/4-20 clearance (Ø 0.257") through part with Ø 0.438" counterbore, 0.250" deep.
- D: 1.200" x 1.200" square hole (with 5/16" circles on corners to allow for machining); cut 0.020" deep and centered as shown. Bottom of channel should be a very flat surface (set finishing pass to minimize machining marks and tool chatter).

ADDITIONAL NOTES:

- 1. Material is 6061-T6 aluminum. Starting block is 4.5" x 7.75" x 1".
- 2. Standard tolerance is 0.005" unless otherwise noted.

FRONT VIEW




UNIBODY LITTROW LASER -- BASEPLATE

E. COOK, P. MARTIN, D. STECK

2/24/10

TOP VIEW



FRONT VIEW

NOTES:

- A: 8-32 clearance through part (Ø 0.177"), for mounting lids to main cavity.
- B: 8-32 tapped through part, for mounting lower lid to baseplate.
- C: Ø 0.177" hole through part.
- D: 1.750" x 1.350" x 0.080" deep rectangular hole with Ø 3/8" fillets, and centered as shown. Dimensions not critical.
- E: 1.600" x 0.500" x 0.005" deep rectangular hole with Ø 3/8" fillets, inset with a 1.500" x 0.250" x 0.010" deep rectangular hole with Ø 1/4" fillets, rotated 45° relative to rest of part, and centered as shown. Dimensions not critical. (Inset border to be used to align grating arm.)
- F: 0.115" wide flat-bottom channel, 0.080" deep, oriented as shown. Channel is for a 3/32" thick, 4.5" inner diameter O-ring.
- G: Ø 7/32" flat-bottom hole, 0.055" deep, for a 1/16" thick, 5/64" inner diameter O-ring.

ADDITIONAL NOTES:

1. Material is 6061-T6 aluminum. Starting block is 4.48" x 6" x 0.75".
2. Standard tolerance is 0.005" unless otherwise noted.

UNIBODY LITTROW LASER -- CAVITY LIDS

E. COOK, P. MARTIN, D. STECK

2/24/10

- A: 4-40 clearance, 0.655" deep; 4-40 tapped through remaining material, as shown.
- B: 8-32 tapped through to hole G.
- C: 4-40 clearance, through to hole B (for venting).
- D: 4-40 clearance, through to slot F, with 0.230" deep counterbore
- E: 4-40 tapped, with maximum thread depth possible.
- F: Gap is centered vertically; dimension not critical.
- G: $\varnothing 0.580" +0.005" / -0.000"$ through.
- H: $\varnothing 0.187"$ hole, 0.140" deep with flat bottom (use 3/16" end mill).
- I: $\varnothing 0.094"$ hole, 0.375" deep; shape of bottom not critical.
- J: $\varnothing 0.313"$ section removed from corners as shown; size and dimension not critical.

2/24/10

1. Material is 6061-T6 aluminum. Starting block is 1.40"x0.78"x1.08".
2. Standard tolerance is 0.005" unless otherwise noted.
3. Surfaces labeled "contact surface" should be made very flat (i.e. cut with a fly cutter then lap flat).

[illegible]

FRONT VIEW

Dimensions and labels for the front view:

- Vertical dimensions (from top):
 - 0.780" (from top to the start of the contact surface)
 - 0.655" (from top to the center of the hole)
 - 0.390" (to relief center)
 - 0.230" (from the center of the hole to the bottom)
- Horizontal dimensions (from left):
 - 0.539" (from left to the center of the hole)
 - 0.924" (from left to the right edge)
- Labels: A, B, C, D, E, F, G, H, I, J.
- Feature: contact surface (indicated by arrows pointing to the top and bottom edges of the part).

RIGHT SIDE VIEW

0.390" (to center of gap)

0.055"

F

0.156"


0.469"

D

E

J

TOP VIEW



FRONT VIEW

NOTES:

- A: 8-32 clearance through part ($\varnothing 0.177"$), for mounting lids to main cavity.
- B: 8-32 tapped through part.
- C: 0.115" wide flat-bottom channel, 0.080" deep, oriented as shown. Channel is for a 3/32" thick, 4.5" inner diameter O-ring.






ADDITIONAL NOTES:

1. Material is 6061-T6 aluminum. Starting block is 4.48" x 6" x 0.75".
2. Standard tolerance is 0.005" unless otherwise noted.

UNIBODY LITTROW LASER -- NEW TOP LID

E. COOK, P. MARTIN, D. STECK

2/24/10



UNIBODY LITTROW LASER -- ISOLATOR ADAPTER II

E. COOK, P. MARTIN, D. STECK

09/24/10

NOTES:

- Cavity thru piece, corner fillets $\varnothing 0.250"$
- 8-32 clearance, extra loose fit ($\varnothing 0.250"$), with loose counterbore $\varnothing 0.375"$, $0.875"$ deep (screw requires a $0.310"$ outer diameter washer for assembly). (x4)
- 4-40 tapped $0.5"$ deep (x4, located on square side length $1"$ rotated 5 deg clockwise). Holes not included in side view for clarity.
- 8-32 clearance, free fit, to $0.250"$ deep, then 8-32 tapped through to cavity A.
- $0.500"$ wide relief cut, $0.020"$ deep. On back of part and centered as shown.
- $0.750"$ wide relief cut, $0.020"$ deep. On front of part and centered as shown.


PERIPHERALS:

- OFR body type II isolator, Thorlabs P/N IO-3D-(wavelength)-VLP
- Fiber coupler assembly: tilt plate with FC connectorized fiber port, Oz Optics
- Fiber coupler assembly to laser head adapter Oz Optics adapter #15.
- 8-32 x $1"$ ss socket-head cap screw, w/ narrow profile ($\varnothing 0.310"$ OD) washer.


ADDITIONAL NOTES:

- Material is 6061-T6 aluminum. Starting block is $1.75" \times 2.05" \times 1.60"$.
- Standard tolerance is $0.005"$ unless otherwise noted.
- Surfaces marked "contact surface" must be made very flat (finishing pass with end mill, as little chatter as possible, lapped).


TOP VIEW





FRONT VIEW



SIDE VIEW



ASSEMBLY



NOTES:

- Cavity thru piece, corner fillets $\varnothing 0.125$ "
- 8-32 clearance, extra loose fit ($\varnothing 0.250$ "), with loose counterbore $\varnothing 0.375$ ", 0.250" deep (screw requires a 0.310" outer diameter washer for assembly). (x4)
- 4-40 tapped through part (x4, located on square side length 1" rotated 5 deg clockwise). Holes not included in side view for clarity.
- 8-32 clearance, free fit, to 0.450" deep, then 8-32 tapped through to cavity A.
- 0.500" wide relief cut, 0.020" deep. On back of part and centered as shown.
- 0.750" wide relief cut, 0.020" deep. On front of part and centered as shown.

PERIPHERALS:


- OFR tablet optical isolator, Thorlabs P/N IO-D-780-VLP
- Fiber coupler assembly: tilt plate with FC connectorized fiber port, Oz Optics P/N
- Fiber coupler assembly to laser head adapter Oz Optics adapter #15.
- 8-32 x 0.375" ss socket-head cap screw, w / narrow profile ($\varnothing 0.310$ " OD) washer.

ADDITIONAL NOTES:


- Material is 6061-T6 aluminum. Starting block is 1.75" x 2.05" x .375".
- Standard tolerance is 0.005" unless otherwise noted.
- Surfaces marked "contact surface" must be made very flat (finishing pass with end mill, as little chatter as possible, lapped).

UNIBODY LITTROW LASER -- CAVITY-COUPLER ADAPTER I

TOP VIEW



FRONT VIEW




NOTES:

- A: 8-32 tapped holes for mounting lids.
- B: $\text{Ø } 1/4$ " holes for venting screws.
- C: $\text{Ø } 0.177$ " hole to pass TEC current wires to underside of main cavity.
- D: Five $\text{Ø } 0.063$ " holes to function as wire feedthroughs.
- E: Shelf for laser-head protection circuit board.
- F: $1/8$ " deep venting channel, which also functions to run wires to the piezo and temperature sensors.

PERIPHERALS:

- I: Diode collimation tube with optic; Thorlabs P/N LT230P-B.
- II: Holographic diffraction grating, lines/mm determined by desired wavelength. Custom size (12mm x 6mm x 3mm) available through Newport.
- III: AR coated anamorphic prism pair; Thorlabs P/N PS871-B.
- IV: Oz Optics pigtailed PM fiber coupler (with hardware).
- V: Low-voltage stacked Piezoelectric actuator from Noliac; P/N SCMA (5 mm x 5 mm x 10 mm; 60 V max voltage; 1000 N blocking force).
- VI: $1/4$ -100 fine adjustment screw, sleeve diameter $\text{Ø } 0.343 \pm 0.001$ "; New Focus P/N 9376-K. Cut hole $\text{Ø } 0.345 \pm 0.001$ " for tight fit.
- VII: D-sub 15 contact female connector, shell size E.
- VIII: Built-in $1/4$ " vacuum seal-off valve (see Cryocomp P/N V1021-1) to be used with a valve operator (Crycomp P/N V1025-3).
- IX: $3/8$ -24 x 0.5" stainless steel socket-head cap screw, with $\text{Ø } 3/8$ ID $1/16$ " thick Viton O-ring.
- X: 4-40 x 0.25" stainless steel socket-head cap screw.
- XI: 8-32 x 0.375" stainless steel socket-head cap screw.
- XII: 8-32 x 0.375" stainless steel socket-head cap screw, with narrow profile ($\text{Ø } 0.310$ " OD) washer.
- XIII: Optical isolator adapter plate (see additional drawings).
- XIV: Viton O-ring, 4-1/2" ID $3/32$ " thick, McMaster P/N 1201T827. Inserted in grooves on lids.

UNIBODY LITTROW LASER -- ASSEMBLY DRAWING



UNIBODY LITTROW LASER -- FULL ASSEMBLY DRAWING

E. COOK, P. MARTIN, D. STECK

3/24/11